

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
4 August 2005 (04.08.2005)


PCT

(10) International Publication Number
WO 2005/070132 A2

- (51) International Patent Classification: Not classified (74) Agent: WIEDMANN, Alfred, K., Jr.; Santangelo Law Offices, P.C., 125 South Howes, Third Floor, Fort Collins, CO 80521 (US).
- (21) International Application Number: PCT/US2005/000768
- (22) International Filing Date: 14 January 2005 (14.01.2005)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
60/536,791 14 January 2004 (14.01.2004) US
- (71) Applicant (for all designated States except US): ULTIMATE SUPPORT SYSTEMS, INC. [US/US]; 2506 Zurich Road, Fort Collins, CO 80524 (US).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): EASON, Donald, H. [US/US]; 1909 Turnberry Road, Fort Collins, CO 80524 (US).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,

[Continued on next page]

(54) Title: TELESCOPING MEMBER METHODS AND APPARATUS



(57) Abstract: The inventive technology may relate to a retention apparatus (1) that in at least one embodiment comprises a compression sleeve element (2) established at least partially 5 around portions of a first elongated member (6) that telescopes from a larger elongated member (8) in which it may nest. A relative motion obstruction element (4) may disallow only certain types of motion, e.g., rotational and axial, of the compression sleeve element relative to the elongated members around which it may be at least partially established. As it instead may be the compression enhancement element (3) - which may be used to 10 generate a retaining compression force element - that prevents perpendicular displacement of the compression sleeve element, deactivation and effective disengagement of the compression enhancement element may allow for a quick removal of the compression sleeve element without requiring that it be slid off an end of either elongated member.

BEST AVAILABLE COPY

WO 2005/070132 A2



FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO,
SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN,
GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— *without international search report and to be republished
upon receipt of that report*

Declaration under Rule 4.17:

— *of inventorship (Rule 4.17(iv)) for US only*

*For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.*

TELESCOPING MEMBER METHODS AND APPARATUS

This is an international application that claims benefit of and priority to United
5 States Provisional Application, 60/536,791, filed January 14, 2004, incorporated herein by
reference.

TECHNICAL FIELD

10 The technical field to which certain embodiments of the inventive technology
relate is releasable retention of adjustable telescoping members.

DISCLOSURE OF INVENTION

15 Generally, the inventive technology disclosed herein relates to a novel and useful
retention apparatus for telescoping members, the apparatus usable to hold members in a
desired fixed relative position. Applications of the inventive apparatus and methods
include when and wherever telescoping member capability is desired, such as adjustable
stands (e.g., musical instrument stands) or reconfigurable support apparatus generally.

20

BACKGROUND

Some considerations relative to the use of telescoping member retention apparatus
will be discussed to facilitate an understanding of the relevant technology. Telescoping
25 members, often but not always telescoping tubes, frequently are found with apparatus that
enable the retention of the two members in a desired relative position. Indeed, there are
many such retention apparatus. But prior art apparatus, as evolved as they may be, still are
not without their problems. Whether the problems that inhere in such technology relate to
limitations associated with adequately securing the apparatus to the larger member in
30 which the smaller member is nested (whether while the apparatus is operating to relatively
retain the members or while the apparatus is in an adjustment configuration), and/or have a
complexity of design that compromises operation, durability or repair speed, prior art
apparatus often leave users dissatisfied. Certain embodiments of the present inventive
technology may solve one or more of these problems, or at least relieve them to a
35 noticeable extent.

BRIEF DESCRIPTIONS OF THE DRAWINGS

Fig. 1 shows an exploded view of an embodiment of the inventive apparatus, in addition to
5 elongated members.

Fig. 2 shows an exploded view of an embodiment of the inventive apparatus including an
annular gap filler, in addition to elongated members.

10 Fig. 3 shows a cut-away view of an embodiment of the inventive apparatus in retention
configuration as is exhibited upon activation of the compression enhancement element.

Fig. 4 shows a view of a fully assembled embodiment of the inventive apparatus (with
annular gap filler) in retention configuration.

15 Fig. 5 shows a view of a fully assembled embodiment of the inventive apparatus in
retention configuration.

Fig. 6 shows a view of a fully assembled embodiment of the inventive apparatus (with
20 phantom tubing) in retention configuration.

Fig. 7 shows an exploded view of a disassembled, non-levered embodiment of the
inventive apparatus.

25 MODES FOR CARRYING OUT THE INVENTION

The present inventive technology includes a variety of aspects, which may be
combined in different ways. The following descriptions are provided to list elements and
describe some of the embodiments of the present inventive technology. These elements
30 are listed with initial embodiments, however it should be understood that they may be
combined in any manner and in any number to create additional embodiments. The
variously described examples and preferred embodiments should not be construed to limit
the present inventive technology to only the explicitly described systems, techniques, and
applications. Further, this description should further be understood to support and
35 encompass descriptions and claims of all the various embodiments, systems, techniques,

methods, devices, and applications with any number of the disclosed elements, with each element alone, and also with any and all various permutations and combinations of all elements in this or any subsequent application.

5 In at least one embodiment of the inventive technology, a retention apparatus (1) may comprise a compression sleeve element (2), a compression enhancement element (3), and a relative motion obstruction element (4). The compression sleeve element, whether it includes one or more parts, may be adapted to at least partially surround a first portion (5) of a first elongated member (6) and a second portion (7) of a larger elongated member (8),
10 where a third portion (9) of the first elongated member may be nested in at least a fourth portion (10) of the larger elongated member. Such third and fourth portions of the elongated members may be co-axial. An elongated member is deemed a larger elongated member whenever it can have nested in it (meaning at least a portion of it) a portion of a different elongated member; the elongated member that has the different elongated
15 member nested within is larger than that nested member. Such nesting is common in telescoping apparatus such as telescoping tubes. Indeed in some embodiments, each the first elongated member and the larger elongated member may be hollow tubes, whether circular in cross-section or not, although only the fourth portion of the larger elongated member need be hollow. It should be understood that the term hollow, as used herein, is a
20 broad term that describes something or a part thereof that is not entirely solid and defines an inner space (whether that space be cylindrical, tubular or have some other shape). It should also be understood that the term elongated member is a broad term that describes, e.g., any structural member that has a length dimension that dominates its width (e.g., where the length of the member is at least twice its width). Further, it should be noted that
25 the elongated members need not be established vertically during operation, as angled or sideways established configurations are also part of the inventive technology. Elongated members also need not be straight along their entire lengths.

The term "at least partially surround" connotes at least partial, opposing
30 establishment of one part or structure around another (see, e.g., Fig. 1). The compression sleeve element may have a first elongated member compression surface (11) and a larger elongated compression member surface (12) that act to transfer a compression force to the first elongated member and the larger elongated member, respectively. In some embodiments, the first elongated member compression surface may be an inner part of an
35 inwardly projecting, annular (or partially annular) lip that overhangs at least part of an

edge of the larger elongated member. Additionally, for purposes relative to clarity of description of the inventive technology, the third portion of the first elongated member may be the to have a first longitudinal axis (13) and the at least a fourth portion of the larger elongated member may have a second longitudinal axis (14). It should be noted that
5 the term "at least a fourth portion" may be used because, indeed, it may be that in some embodiments of the inventive technology the entire larger elongated member may have nested within it the third portion of the first elongated member.

The inventive technology may include a compression enhancement element that is
10 situated so that, upon its activation (e.g., upon rotation of a clamping lever (15) of a clamp (16) having an eccentric cam (1&) and/or sufficient rotation of a threaded bolt as in cases where there is no clamping lever (see Fig. 7), it forces the larger elongated member compression surface towards the larger elongated member, and the first elongated member compression surface towards a site (18) on the first elongated member that is not within
15 the larger elongated member, thereby retaining the first elongated member in fixed position relative to the larger elongated member. The term "forces...towards" describes that which occurs whenever a compressive force is generated; the term is broad enough to cover the case where each of the aforementioned compression surfaces are either in direct contact with a respective elongated member or not. Similarly, one part may surround or
20 partially surround another (or be around or be partially around another) notwithstanding the absence of direct contact between the two parts. Of course, direct contact may be absent where there is established within at least part of the larger elongated member (e.g., a second portion thereof) an annular gap filler (19) whose purpose may be to fill a space between part of the larger elongated member and part of the first elongated member nested
25 within. Often, however, the first elongated member compression surface is adequately sized (e.g., small enough in diameter) to directly contact the first elongated member, rendering an annular gap filler unnecessary. Of course, the use of significantly differently sized tubes as part of a telescoping apparatus is one way in which this problem may arise. It should be understood that, as used herein, annular does not require a cross-section
30 having concentric or even circular inner and/or outer surface cross-section shapes. Indeed, as but one example, the inner shape may be vertically ribbed such that it contacts the first elongated member at only intermittent vertical sections (e.g., see Fig. 2).

A relative motion obstruction element (4) may also be part of the inventive
35 apparatus and may be adapted to prevent only axial and rotational motion of the

compression sleeve element relative to the larger elongated member. The relative motion obstruction element may be established as part of the compression sleeve element and the larger elongated member. As such, it may prevent motion of the compression sleeve element relative to the larger elongated member. It should be noted that the term element
5 as used in this application may describe not only one part or structure, but also a plurality of parts or structures (20) e.g., that make up a device. As such, in at least one embodiment of the inventive technology, the relative motion obstruction element may include at least one projection (21) (e.g., a post, which may have any cross-sectional shape and which may project inwardly from the compression sleeve element), and at least one recess (e.g. a
10 hole) sized to receive the post, thereby preventing axial and rotational motion. Of course, a projection may be engaged with a recess upon establishment of the projection in the recess.

It should be noted also that the relative motion obstruction element is not intended
15 to prevent all types of motion of the compression sleeve element relative to the larger elongated member. Indeed, in the preferred embodiments, the relative motion obstruction element, even when engaged, does not prevent perpendicular (22) (e.g., radial) displacement of the compression enhancement element relative to the second longitudinal axis. Such perpendicular displacement is prevented by the compression enhancement
20 element when activated. That such motion is prevented by the compression enhancement element (and not by the relative motion obstruction element) may enable the compression sleeve element to be easily removed upon deactivation of and effective disengagement of the compression enhancement element. It should be noted that perpendicular displacement occurs whenever the displacement has any component in a perpendicular
25 direction.

Deactivation of the compression enhancement element connotes manipulation of the compression retention element only such that the compressive force that retains the first elongated member in fixed relative position is removed. Deactivation is a step that is
30 different and exclusive of the step of effective disengagement, discussed below. In embodiments where there is no clamping lever, deactivation may involve the sufficient loosening of a bolt to just release the compressive force that retains the first elongated member in fixed position relative to the larger elongated member. In embodiments where there is a clamping lever (see, e.g. Fig. 1), deactivation may only involve the manipulation
35 of the lever to just remove the compressive force. Even in embodiments where there is a

clamping lever, there may be a threaded bolt (24) and nut (25) (the lever, nut, bolt and collar all considered parts of the compression enhancement element), but in such levered designs, activation and deactivation of the compression enhancement element typically does not involve manipulation of that bolt or nut. After deactivation, the first elongated member may be movable relative to the larger elongated member.

Effective engagement connotes at the least the establishment of the compression enhancement element at least partially around the compression sleeve element such that the compression enhancement element does not fall from this position because of gravity or other anticipated force and such that it cannot be perpendicularly removed from this position. In cases where the compression enhancement element is non-levered, it may involve merely the establishment of a bolt into receptive holes and the sufficient initiation of threading of the bolt into a nut. In cases where the compression enhancement element is levered, it may involve the establishment of a bolt into receptive holes and the sufficient initiation of threading of the bolt into a nut so a subsequent operation of the lever effects a compressive force to retain the first elongated member in fixed position relative to the larger elongated member.

Effective disengagement, which may not necessarily be the reverse of effective engagement, may involve different steps depending on the type of compression enhancement element. In levered designs, effective disengagement may merely involve the local displacement (after deactivation, of course) of the compression enhancement element merely to expose the compression sleeve element so that it may be removed without obstruction. In non-levered designs, effective disengagement may involve the removal of a bolt from holes through which it may pass (and might not require any local displacement of the compression enhancement element). Indeed, in such a design, the removal of the compression enhancement element may occur simultaneously with the removal of the compression sleeve element. It is of note that although the preferred type of non-levered design involves a compression enhancement element that is at least partially integral with the compression sleeve element (see, e.g. Fig. 7), collared designs (where the compression enhancement element is not integral with the compression sleeve element) that are not levered are also within the ambit of the inventive technology.

Upon deactivation and effective disengagement of the compression enhancement element, the compression sleeve element may have the advantage of perpendicular

displaceability, and perpendicular removability, allowing for a quick disassembly without the need to slide the compression enhancement element either along either of the elongated members. Of course, perpendicular may be relative to the second longitudinal axis, and include radial in cases where the first elongated member is substantially circular in cross-section.

What may facilitate such quick removal may be that the compression sleeve element is separated along at least one split (26) from a first elongated member proximate edge (27) of the compression sleeve element to a larger elongated member proximate edge (28) of the compression sleeve element. Where there are two (or more) splits that separates the compression sleeve element in two (or more) parts (see, e.g. Fig. 1), the compression sleeve element might not require any application of manual force (or it may require only a slight application of manual force) to remove it; where there is only one split (see, e.g., Fig. 7), to remove the compression sleeve element it may be necessary to apply a force to overcome the obstructive effect posed by the second portion of the larger elongated member.

It should also be noted that the compression sleeve element may be shaped to provide a clearance (29) from the larger elongated member between the first elongated member compression surface and the larger elongated member compression surface. Such clearance may ensure that the compression force acts against the first elongated member as intended (instead of being blocked by the larger elongated member). In preferred embodiments, the first elongated member compression surface has a characteristic dimension (e.g., a radius) that is less than a characteristic dimension of the larger elongated member compression surface.

Of course, as is the purpose of many telescoping member retention apparatus, before activation of the compression enhancement element the first elongated member may be adjusted to a desired position relative to the larger elongated member. Then, upon activation of the compression enhancement element, it may be held in this position.

As can be easily understood from the foregoing, the basic concepts of the present invention may be embodied in a variety of ways. It involves (but is not limited to) both retention techniques as well as devices to accomplish the appropriate retention. In this application, the support or attachment techniques are disclosed as part of the results shown

to be achieved by the various devices described and as steps which are inherent to utilization. They are simply the natural result of utilizing the devices as intended and described. In addition, while some devices are disclosed, it should be understood that these not only accomplish certain methods but also can be varied in a number of ways.

5 Importantly, as to all of the foregoing, all of these facets should be understood to be encompassed by this disclosure.

The discussion included in this patent application is intended to serve as a basic description. The reader should be aware that the specific discussion may not explicitly

10 describe all embodiments possible; many alternatives are implicit. It also may not fully explain the generic nature of the invention and may not explicitly show how each feature or element can actually be representative of a broader function or of a great variety of alternative or equivalent elements. Again, these are implicitly included in this disclosure. Where the invention is described in device-oriented terminology, each element of the

15 device implicitly performs a function. Apparatus claims may not only be included for the device described, but also method or process claims may be included to address the functions the invention and each element performs. Neither the description nor the terminology is intended to limit the scope of the claims that will be included in any subsequent patent application.

20

It should also be understood that a variety of changes may be made without departing from the essence of the invention. Such changes are also implicitly included in the description. They still fall within the scope of this invention. A broad disclosure encompassing both the explicit embodiment(s) shown, the great variety of implicit

25 alternative embodiments, and the broad methods or processes and the like are encompassed by this disclosure and may be relied upon when drafting the claims for any subsequent patent application. It should be understood that such language changes and broader or more detailed claiming may be accomplished at a later date (such as by any required deadline) or in the event the applicant subsequently seeks a patent filing based on

30 this filing. With this understanding, the reader should be aware that this disclosure is to be understood to support any subsequently filed patent application that may seek examination of as broad a base of claims as deemed within the applicant's right and may be designed to yield a patent covering numerous aspects of the invention both independently and as an overall system.

35

Further, each of the various elements of the invention and claims may also be achieved in a variety of manners. Additionally, when used, the term "element" is to be understood as encompassing individual or singular, as well as plural structures that may or may not be physically connected. This disclosure should be understood to encompass each such variation, be it a variation of an embodiment of any apparatus embodiment, a method or process embodiment, or even merely a variation of any element of these. Particularly, it should be understood that as the disclosure relates to elements of the invention, the words for each element may be expressed by equivalent apparatus terms or method terms -- even if only the function or result is the same. Such equivalent, broader, or even more generic terms should be considered to be encompassed in the description of each element or action. Such terms can be substituted where desired to make explicit the implicitly broad coverage to which this invention is entitled. As but one example, it should be understood that all actions may be expressed as a means for taking that action or as an element which causes that action. Similarly, each physical element disclosed should be understood to encompass a disclosure of the action which that physical element facilitates. Regarding this last aspect, as but one example, the disclosure of a "clamp" should be understood to encompass disclosure of the act of "clamping" -- whether explicitly discussed or not -- and, conversely, were there effectively disclosure of the act of "clamping", such a disclosure should be understood to encompass disclosure of a "clamp" and even a "means for clamping" Such changes and alternative terms are to be understood to be explicitly included in the description.

Any acts of law, statutes, regulations, or rules mentioned in this application for patent; or patents, publications, or other references mentioned in this provisional application for patent are hereby incorporated by reference. In addition, as to each term used it should be understood that unless its utilization in this application is inconsistent with such interpretation, common dictionary definitions should be understood as incorporated for each term and all definitions, alternative terms, and synonyms such as contained in the Random House Webster's Unabridged Dictionary, second edition are hereby incorporated by reference. Finally, all references listed in the list of References To Be Incorporated By Reference In Accordance With The Provisional Patent Application or other information statement filed with the application are hereby appended and hereby incorporated by reference, however, as to each of the above, to the extent that such information or statements incorporated by reference might be considered inconsistent with

the patenting of this/these invention(s) such statements are expressly not to be considered as made by the applicant(s).

I. US Patent Documents

5

DOCUMENT NO. & KIND CODE (if known)	PUBLICATION DATE (mm/dd/yyyy)	PATENTEE APPLICANT NAME	OR
Des. 295,471	05/03/1988	Lindskog	
Des. 306,943	04/03/1990	Hodge et al.	
Des. 320,034	09/17/1991	Brooks et al.	
Des. 326,969	06/16/1992	Eason et al.	
Des. 329,342	09/15/1992	Schoenig	
Des. 336,099	06/01/1993	Schoenig	
Des. 356,901	04/04/1995	Schoenig et al.	
Des. 358,048	05/09/1995	Schoenig et al.	
Des. 364,281	11/21/1995	Eason	
Des. 372,691	08/13/1996	Eason	
Des. 375,639	11/19/1996	House et al.	
Des. 400,565	11/03/1998	Ahl	
Des. 400,735	11/10/1998	House et al.	
Des. 416,464	11/16/1999	Eason	
Des. 421,447	03/07/2000	Eason et al.	
Des. 435,365	12/26/2000	Eason et al.	
D 450,339 S	11/13/2001	Eason	
D 492,587 S	07/06/2004	Eason	
D 493,363 S	07/27/2004	Eason	
D 742,453	10/27/1903	Lake	
5,911,523	06/15/1999	Burchart	
1,309,375	06/08/1919	Taylor	
1,376,593	05/03/1921	Tuttle	
1,970,624	08/21/1934	Recker	
2,902,592	09/01/1959	Cole et al.	
3,463,520	08/26/1969	Turro	
3,603,623	09/07/1971	Widman	
3,604,734	09/14/1971	Friedman et al.	
3,823,245	07/09/1974	Suzuki	
4,102,219	07/25/1978	Plamper	
4,111,575	09/05/1978	Hoshino	
4,140,415	02/20/1979	Koyamato	
4,185,936	01/29/1980	Takahaski	
4,227,049	10/07/1980	Thomson et al.	
4,405,107	09/20/1983	Clyburn	
4,430,017	02/07/1984	Stefancich	
4,479,414	10/30/1984	Willis	

4,579,229	04/01/1986	Porcaro et al.
4,593,422	06/10/1986	Wolpert, Jr. et al.
4,593,596	06/10/1986	Gauger
4,596,484	06/24/1986	Nakatani
4,606,525	08/19/1986	Lombardi
4,671,479	06/09/1987	Johnson et al.
4,691,611	09/08/1987	May
4,744,690	05/17/1988	Hsieh
4,761,092	08/02/1988	Nakatani
4,768,798	09/06/1988	Reed et al.
4,770,380	09/13/1988	Eason et al.
4,818,135	04/04/1989	Desjardins
5,029,796	07/09/1991	Schoenig
5,048,789	09/17/1991	Eason et al.
5,063,821	11/12/1991	Battle
5,069,254	12/03/1991	Vogelsang
5,140,889	08/25/1992	Segan et al.
5,154,449	10/13/1992	Suei/Long
5,161,761	11/10/1992	May
5,182,416	01/26/1993	Schweizer
5,337,646	08/16/1994	Austin
5,520,292	05/28/1996	Lombardi
5,531,148	07/02/1996	Wilson
5,570,968	11/05/1996	Sassmannshausen et al.
5,726,369	03/10/1998	Gilday
5,744,738	04/28/1998	Gatzen
5,857,649	01/12/1999	Eason
5,929,355	07/27/1999	Adinolfi
5,949,008	09/07/1999	Augsburger
5,996,814	12/07/1999	Workman et al.
6,062,396	05/16/2000	Eason
6,283,421 B1	09/04/2001	Eason et al.
6,343,802 B1	02/05/2002	Workman et al.
6,375,135 B1	04/23/2002	Eason et al.
6,610,916	08/26/2003	Torrez
6,653,540 B2	11/25/2003	Izen et al.
6,719,257 B1	04/13/2004	Greene et al.
6,722,810 B1	04/20/2004	Tachikawa
6,789,772 B2	09/14/2004	Eason
6,814,332 B2	11/09/2004	Eason
6,856,253	12/24/1974	Seebinger

II. FOREIGN PATENT DOCUMENTS

Foreign Patent Document Country Code, Number, Kind Code (if known)	PUB'N DATE mm/dd/yyyy	PATENTEE OR APPLICANT NAME
WO 95/20107 (PCT/NZ95/00004)	07/27/1995	Interlock Industries Limited

III. OTHER DOCUMENTS

5

Gibraltar Hardware, "Rack Factory" #GRS400C, Gibraltarhardware.com, January 9, 2004, 2 pages
Gibraltar Hardware, "Rack Factory" GRS400C, Gibraltarhardware.com, October 25, 2004, 2 pages, Ride/Crash Overhead Station and Xhat to boom and Rack Options
Gibraltar Hardware, "Rack Factory" GRS400C, Gibraltarhardware.com, October 25, 2004, 2 pages, Mini Snare on Curved Support Tube Option
Gibraltar Hardware, "Rack Factory" GRS400C and GRS150C, Gibraltarhardware.com, October 25, 2004, 2 pages, Boom Arm to Rack and Multi/Cymbal Overhead Station Options
Gibraltar Hardware, "Rack Factory" GRS250C, Gibraltarhardware.com, October 25, 2004, 2 pages, Multi Cymbal Setup to rack, Mini Timbale to Rack, Tambourine to Open Tube, and Percussion Table to Open Tube Options
Gibraltar Hardware, "Rack Factory" GRS350C, Gibraltarhardware.com, October 25, 2004, 2 pages, Triple Cymbal Station to Rack and Large Tom to Rack Options
Pintech, USA, Control the Sound with America's E Drum Color Brochure, 2004, 5 pages
Roland Corporation, roland.com MDS/10RD, printed from website as of 11/5/2004
Roland Corporation, roland.com MDS/8C, printed from website as of 11/5/2004
Roland Corporation, roland.com MDS/6, printed from website as of 11/5/2004
Tama Hardware, PMD300FC Power Tower System, tama.com, January 9, 2004, 1 page
Tama Hardware, PMD800SS Power Tower System, tama.com, January, 9, 2004, 2 pages
Ultimate Support Systems, Inc. 1994 Product Catalog
Ultimate Support Systems, Inc. 1996 Product Catalog
Ultimate Support Systems, Inc. 1999 Product Catalog
Ultimate Support Systems, Inc. 2000 Product Catalog
Ultimate Support Systems, Inc. 2001 Product Catalog
Ultimate Support Systems, Inc. 2002 Product Catalog
Ultimate Support Systems, Inc. 2003 Product Catalog
US Patent Application Number 60/536,791 filed January 14, 2004, 15 pages, 11 drawings
Yamaha Percussion System Drum Rack

Thus, the applicant(s) should be understood to have support to claim and make a statement of invention to at least: i) each of the devices (including support and attachment devices) as herein disclosed and described, ii) the related methods disclosed and described, iii) similar, equivalent, and even implicit variations of each of these devices and methods, iv) those alternative designs which accomplish each of the functions shown as are disclosed and described, v) those alternative designs and methods which accomplish each of the functions shown as are implicit to accomplish that which is disclosed and described,

vi) each feature, component, and step shown as separate and independent inventions, vii) the applications enhanced by the various systems or components disclosed, viii) the resulting products produced by such systems or components, ix) each system, method, and element shown or described as now applied to any specific field or devices mentioned, x) methods and apparatuses substantially as described hereinbefore and with reference to any of the accompanying examples, xi) the various combinations and permutations of each of the elements disclosed, and xii) each potentially dependent claim or concept as a dependency on each and every one of the independent claims or concepts presented.

10 With regard to claims whether now or later presented for examination, it should be understood that for practical reasons and so as to avoid great expansion of the examination burden, the applicant may at any time present only initial claims or perhaps only initial claims with only initial dependencies. Support should be understood to exist to the degree required under new matter laws -- including but not limited to European Patent
15 Convention Article 123(2) and United States Patent Law 35 USC 132 or other such laws-- to permit the addition of any of the various dependencies or other elements presented under one independent claim or concept as dependencies or elements under any other independent claim or concept. In drafting any claims at any time whether in this application or in any subsequent application, it should also be understood that the
20 applicant has intended to capture as full and broad a scope of coverage as legally available. To the extent that insubstantial substitutes are made, to the extent that the applicant did not in fact draft any claim so as to literally encompass any particular embodiment, and to the extent otherwise applicable, the applicant should not be understood to have in any way intended to or actually relinquished such coverage as the
25 applicant simply may not have been able to anticipate all eventualities; one skilled in the art, should not be reasonably expected to have drafted a claim that would have literally encompassed such alternative embodiments.

Further, if or when used, the use of the transitional phrase "comprising" is used to
30 maintain the "open-end" claims herein, according to traditional claim interpretation. Thus, unless the context requires otherwise, it should be understood that the term "comprise" or variations such as "comprises" or "comprising", are intended to imply the inclusion of a stated element or step or group of elements or steps but not the exclusion of any other element or step or group of elements or steps. Such terms should be interpreted in their

most expansive form so as to afford the applicant the broadest coverage legally permissible.

Finally, any claims set forth at any time are hereby incorporated by reference as
5 part of this description of the invention, and the applicant expressly reserves the right to
use all of or a portion of such incorporated content of such claims as additional description
to support any of or all of the claims or any element or component thereof, and the
applicant further expressly reserves the right to move any portion of or all of the
10 incorporated content of such claims or any element or component thereof from the
description into the claims or vice-versa as necessary to define the matter for which
protection is sought by this application or by any subsequent continuation, division, or
continuation-in-part application thereof, or to obtain any benefit of, reduction in fees
pursuant to, or to comply with the patent laws, rules, or regulations of any country or
15 treaty, and such content incorporated by reference shall survive during the entire pendency
of this application including any subsequent continuation, division, or continuation-in-part
application thereof or any reissue or extension thereon.

CLAIMS

What is claimed is:

5 1. A retention apparatus comprising:

- a compression sleeve element:

10 - adapted to at least partially surround a first portion of a first elongated member and a second portion of a larger elongated member, wherein a third portion of said first elongated member is nested in at least a fourth portion of said larger elongated member, and

- having a first elongated member compression surface and a larger elongated member compression surface,

15

- wherein said third portion of said first elongated member has a first longitudinal axis and said at least a fourth portion of said larger elongated member has a second longitudinal axis,

20

- a compression enhancement element established so that, upon activation, it forces said:

- larger elongated member compression surface towards said larger elongated member, and

25

- said first elongated member compression surface towards a site on said first elongated member that is not within said larger elongated member,

said compression apparatus further comprising:

30

- a relative motion obstruction element adapted to prevent only axial and rotational motion of said compression sleeve element relative to said larger elongated member,

- wherein said third portion of said first elongated member and said at least a fourth portion of said larger elongated member are substantially coaxial,

35

- wherein said at least a fourth portion of said larger elongated member is hollow,

- wherein said relative motion obstruction element comprises at least one projection and at least one recess,
 - wherein said compression sleeve element is separated along at least one split from a first elongated member proximate edge of the compression sleeve element to a larger elongated member proximate edge of the compression sleeve element, and
 - wherein said compression sleeve element is perpendicularly displaceable and perpendicularly removable, relative to said second longitudinal axis, from said first elongated member and said larger elongated member upon deactivation of and effective disengagement of said compression enhancement element.
2. A retention apparatus as described in claim 1 wherein said at least one split is parallel to said first longitudinal axis.
3. A retention apparatus as described in claim 1 wherein said at least one split is two splits.
4. A retention apparatus as described in claim 3 wherein each of said two splits is parallel to said first longitudinal axis.
5. A retention apparatus as described in claim 1 wherein said at least one recess is a hole established in said larger elongated member.
6. A retention apparatus as described in claim 1 wherein said at least one projection is a post projecting inwardly from said compression sleeve element.
7. A retention apparatus as described in claim 1 wherein said at least one projection is a post projecting outwardly from said larger elongated member.
8. A retention apparatus as described in claim 1 wherein said compression enhancement element is a clamp having an eccentric cam.
9. A retention apparatus as described in claim 1 wherein said compression sleeve element is shaped to provide a clearance from said larger elongated member

between said first elongated member compression surface and said larger elongated member compression surface.

- 5 10. A retention apparatus as described in claim 1 wherein said compression enhancement element is at least partially integral with said compression sleeve element.
- 10 11. A retention apparatus as described in claim 1 wherein said third portion of said first elongated member has an outer surface sized to fit substantially against an inner surface of said at least a fourth portion of said larger elongated member.
12. A retention apparatus as described in claim 1 wherein said compression sleeve element is radially displaceable and radially removable.
- 15 13. A retention apparatus as described in claim 1 wherein each said first elongated member and said larger elongated member is hollow.
14. A retention apparatus as described in claim 1 wherein said first elongated member compression surface has a characteristic dimension that is less than a characteristic dimension of said larger elongated member compression surface.
- 20 15. A retention apparatus as described in claim 1 wherein effective disengagement of said compression enhancement element comprises local displacement of said compression enhancement element.
- 25 16. A retention apparatus as described in claim 1 wherein said deactivation of said compression enhancement element is achieved upon loosening a bolt of said compression enhancement element.
- 30 17. A retention apparatus as described in claim 1 wherein said deactivation of said compression enhancement element is achieved upon operation of a lever of said compression enhancement element.

18. A retention apparatus as described in claim 1 wherein said effective disengagement of said compression enhancement element is achieved after removal of a nut from a bolt and removal of said bolt from any holes through which it may pass.
- 5 19. A retention apparatus as described in claim 1 further comprising an annular gap filler.
20. A retention apparatus as described in claim 1 wherein said larger elongated member compression surface and said first elongated member compression surface
10 each directly contact one of said elongated members.
21. A retention apparatus as described in claim 1 further comprising said elongated members.
- 15 22. A retention apparatus as described in claim 1 further comprising a support apparatus of which said retention apparatus forms a part.
23. A method comprising the steps of:
- 20 - establishing a compression sleeve element at least partially around a first portion of a first elongated member and a second portion of a larger elongated member; wherein a third portion of said first substantially elongated member nests within at least a fourth portion of said larger elongated member; then
- 25 - effectively engaging a compression enhancement element such that it may be subsequently activated so as to force a larger elongated member compression surface towards said larger elongated member and to force a first elongated member compression surface towards a site on said first elongated member that is not within said larger elongated member; then
- 30 - preventing only axial and rotational motion of said compression sleeve element relative to said larger elongated member by engaging at least one projection with at least one recess of a relative motion obstruction element; then
- adjusting said first elongated member to a desired position relative to said larger elongated member; then
- 35 - activating said compression enhancement element to force said larger elongated member compression surface towards said larger elongated member and to force

- said first elongated member compression surface towards said site on said first elongated member that is not within said larger elongated member, thereby retaining said first elongated member in said desired position; then
- deactivating said compression enhancement element; then
 - 5 - effectively disengaging said compression enhancement element; and then
 - removing said compression sleeve element by displacing said compression sleeve element in a direction that is perpendicular to a longitudinal axis of said fourth portion of said larger elongated element.
- 10 wherein said fourth portion of said larger elongated member is hollow.
24. A method as described in claim 23 wherein said step of deactivating said compression enhancement element comprises the step of unclamping said compression enhancement element by operating a lever
- 15 25. A method as described in claim 23 wherein said step of deactivating said compression enhancement element comprises the step of loosening a bolt
- 20 26. A method as described in claim 23 wherein said step of effectively disengaging said compression enhancement element comprises the step of locally displacing said compression enhancement element
- 25 27. A method as described in claim 23 wherein said step of effectively disengaging said compression enhancement element comprises the step of removing a nut from a bolt and removing said bolt from holes through which it may pass.
28. A method as described in claim 23 wherein said step of effectively engaging a compression enhancement element comprises the step of placing a bolt through a hole and initiation threading of a nut.
- 30 29. A method as described in claim 23 wherein said step of effectively engaging a compression enhancement element comprises the step of effectively engaging a clamp around said compression sleeve element.

30. A method as described in claim 29 wherein said step of effectively engaging a clamp around said compression sleeve element comprises the step of effectively engaging a clamp having an eccentric cam.
- 5 31. A method as described in claim 29 wherein said step of effectively engaging a clamp around said compression sleeve element comprises the step of threading a bolt into a nut such that operation of said lever sufficiently retains said first elongated member in fixed position relative to said larger elongated member.
- 10 32. A method as described in claim 23 wherein said step of preventing only axial and rotational motion of said compression sleeve element relative to said larger elongated member by engaging at least one projection with at least one recess of a relative motion obstruction element comprises the step of engaging at least one projection on an inner surface of said compression sleeve element with at least one
15 recess established on said larger elongated member.
33. A method as described in claim 32 wherein said at least one recess established on said larger elongated member is a hole in said larger elongated member.
- 20 34. A method as described in claim 23 wherein said step of adjusting said first elongated member to a desired position relative to said larger elongated member comprises the step of telescoping said first elongated member.
- 25 35. A method as described in claim 23 wherein said step of activating said compression enhancement element comprises the step of clamping said compression enhancement element.
- 30 36. A method as described in claim 23 wherein said step of activating said compression enhancement element comprises the step of threading a nut and bolt of said compression enhancement element.
- 35 37. A method as described in claim 23 wherein said step of effectively disengaging said compression enhancement element comprises the step of removing a bolt from holes through which it may pass.

38. A method as described in claim 23 wherein said step of effectively disengaging said compression enhancement element comprises the step of locally displacing said compression enhancement element.
- 5 39. A method as described in claim 38 wherein said step of locally displacing said compression enhancement element comprises the step of manually grasping said compression enhancement element and sliding it to expose said compression sleeve element.
- 10 40. A method as described in claim 23 wherein said step of removing said compression sleeve element comprises the step of separating two parts of said compression sleeve element that were oppositely established at least partially around a first portion of a first elongated member and a second portion of a larger elongated member.
- 15 41. A method as described in claim 23 wherein said step of removing said compression sleeve element by displacing said compression sleeve element in a direction that is perpendicular to a longitudinal axis of said fourth portion of said larger elongated element comprises the step of displacing said compression sleeve element in a
- 20 radial direction relative to a longitudinal axis of said fourth portion of said larger elongated element.

1/7




Fig. 1

BEST AVAILABLE COPY

2/7





Fig. 2

3/7



4/7




Fig. 4

BEST AVAILABLE COPY

5/7




Fig. 5

6/7




Fig. 6

7/7




Fig. 7